



F5DW

► Performance characteristics:

Wide application range

Main processing: personalized abutment, glass ceramics, titanium crown and select processing HPP function.

Stable performance

Double support, more stability. The motor seat, bearing seat and machine tool cast iron are integrated, featuring high rigidity, impact resistance and no deformation, so that the pedestal can maintain high rigidity and long service life; Integrated cooling system, which can work for a long time without heating, ensures the machine to run for a long time with high accuracy;

Quality assurance

The key components that affect the quality of the whole machine are imported high-quality accessories from the world's top brands;

Persistent operation

The excellent mechanical structure is the foundation to ensure the mechanical accuracy and rigidity. The international standard full Meehanite cast iron is adopted. It is integrally formed without welding. The original accuracy is still maintained after years of use.

► Technical parameter:



Model	F5DW	
Machine Size	750*470*680mm	
Net Weight	143kg	
Rotation Angle	A:360°,B: ±30°	
Machine Power	3kw	
Spindle	Mode	Dry/wet milling
	Power	0.8kw
	Speed	3,000-60,000rpm
	Tools	8
	Cooling	Air cooling
Materials	Dry	Zirconia, wax, PMMA, PEEK
	Wet	Glass ceramic, etc
Average Milling Time	Crown	12-15min
	Glass Ceramic	10-20min

